



# SpeedMixer™

German Engineering  
by Hauschild

V  
A  
C  
U  
U  
M



*DAC 400.2 / 1100.2*



Please scan  
for more  
information  
about our  
products.





# SpeedMixer™

GermanEngineering  
by Hauschild

## Technical Data

	DAC 400.2 VAC-P	DAC 600. 2 VAC-P	DAC 700. 2 VAC-P	DAC 800. 2 VAC-P
Mixing Capacity Min/Max:	100g ÷ 300g	200g ÷ 500g	200g ÷ 600g	400g ÷ 700g
Speed Min/Max:	800 rpm ÷ 2500 rpm	800 rpm ÷ 2350 rpm	800 rpm ÷ 2100 rpm	800 rpm ÷ 1950 rpm
Mixing Time Min/Max:	5s ÷ 600s	5s ÷ 600s	5s ÷ 600s	5s ÷ 600s
Voltage - Frequency:	230 V – 50/60 Hz	230 V – 50/60 Hz	230 V – 50/60 Hz	230 V – 50/60 Hz
Input Power:	1,2 KW	1,2 KW	1,2 KW	1,2 KW
Height – Open Lid:	1030 mm	1030 mm	1030 mm	1030 mm
Width:	440 mm	440 mm	440 mm	440 mm
Depth:	700 mm	700 mm	700 mm	700 mm
Weight:	90 kg	90 kg	90 kg	90 kg

	DAC 1100. 2 VAC-P
Mixing Capacity Min/Max:	800g ÷ 1000g
Speed Min/Max:	800 rpm ÷ 1600 rpm
Mixing Time Min/Max:	5s ÷ 600s
Voltage - Frequency:	230 V – 50/60 Hz
Input Power:	1,2 KW
Height – Open Lid:	1030 mm
Width:	440 mm
Depth:	700 mm
Weight:	95 kg



Your Notes:

Subject to modifications – Last update 28/08/2018



Hauschild & Co. KG  
 Waterkamp 1 · 59075 Hamm / Germany  
 Phone +49 (0)2381 48205-0  
 Telefax +49 (0)2381 48205-17  
 E-Mail info@speedmixer.de  
 www.speedmixer.de